

"WEIGHT ONLY" SCALES



PS-50 / PS-60

- Capacity / Accuracy:
PS-50: 3 kg - 0,5 g / 6 kg - 1 g / 15 kg - 2 g.
PS-60: 3 kg - 1 g / 6 kg - 2 g / 15 kg - 5 g.
- Back-light LCD display (5 Digits 20 mm high) in PS-50 model and LED in PS-60 model.
- Splash proof housing (PS-50: similar IP-64, PS-60: similar IP-68).
- Programs: weight, unit conversion, auto power off function.
- Mains and internal battery.
- Dimensions: 23,5 x 24,0 cm; plate (stainless steel): 23,0 x 19,0 cm.

STAINLESS STEEL "WEIGHT ONLY" SCALES

- Capacity / Accuracy: 10 kg - 2 g.
- Stainless steel housing and plate.
- LCD back-light display, with 17 mm digits.
- Tare, unit conversion (kg/lb), auto-off and checkweigher (under-over), with alarm.
- RS-232 communications.
- Power: mains and rechargeable battery (range: up to 100 hours, depending on use conditions).
- Dimensions: 24,5 x 25,0 cm; plate: 24,5 x 19,0 cm (width x length).

SW-100



PRICE COMPUTING SCALES



SC-100

- Capacity / Accuracy: 20 kg - 5 g.
- Stainless steel housing and plate.
- Double LCD back-light display (frontal/back), with 13 mm digits (for weight/amount) and 12 mm (for price).
- 100 PLUs, 9 presets. Fix price, tare and auto-off features.
- Power: mains and rechargeable battery (range: up to 30 hours, depending on use conditions).
- Dimensions: 30,5 x 29,0 cm; plate: 30,5 x 22,0 cm (width x length).
- CE approval.

COUNTING SCALES

- Capacity / Accuracy: 3 kg - 0,1 g / 6 kg - 0,2 g / 15 kg - 0,5 g / 30 kg - 1 g.
- Internal resolution: 1/600.000
- 3 LCD back-light displays. 5 Digits 20 mm high.
- Programs: piece counting, preset tares, pieces checking alarm, accumulation.
- Mains and internal battery.
- Dimensions: 32,0 x 34,0 cm; plate (stainless steel): 29,5 x 22,5 cm.

PC-50



PRECISION SCALES



PB-60

- Capacity / Accuracy:
300 g - 0,005 g / 600 g - 0,01 g / 1.500 g - 0,02 g / 3.000 g - 0,05 g.
- Back-light LCD display. 5 Digits 15 mm high.
- Programs: piece counting, percent weighing, accumulation, unit conversion.
- Mains and internal battery.
- Stainless steel plate. Wind shield included in 300 and 600 g models.
- Dimensions: 19,0 x 23,0 cm.

SINGLE LOADCELL PLATFORMS

- High robustness construction in steel (S-3545 and L-6080) or aluminium (M-4252).
- Stainless steel plate.
- Connectable to CELY and DIBAL indicators (others, please consult).

S-3545 M-4252 L-6080



Model	S-3545	M-4252	L-6080
Dimensions (cm)	35 x 45	42 x 52	60 x 80
Capacity (kg)	30, 60, 150	60, 150, 300	300, 600



WEIGHT INDICATORS

VC-50

- Connectable to platforms up to 4 loadcells.
- ABS housing, high robustness.
- Back-light LCD display. 5 Digits 24 mm high.
- Programs: piece counting, checkweighing, accumulation, unit conversion.
- Mains and internal battery.
- Capacity / display resolution: programmable up to 15.000 divisions.

WEIGHT INDICATORS

- Back-light LCD display. 6 digits 22 mm high.
- Programs: zero, tare, unit conversion (kg/lb), accumulation, gross/net weight, and weight control with alarm.
- Connection: up to 4 loadcells platforms (minimum impedance: 75 Ohms).
- Robust ABS housing.
- Internal resolution: 1/6.000.
- 9 VDC adapter included. Also available version with rechargeable battery.

RW-I



WEIGHT INDICATORS WITH LARGE DIGITS

BW+

- Back-light LCD display, 5 ½ digits 52 mm high.
- Programs: zero, tare, unit conversion (kg/lb), accumulation, auto-off, keyboard blockade, weight control with alarm, animal weighing.
- Connection: up to 4 loadcells platforms (minimum impedance: 75 Ohms).
- Robust ABS housing.
- Internal resolution: 1/30.000.
- Power: mains and rechargeable battery (range: up to 70 hours, depending on use conditions).



INDUSTRIAL SCALES (INDICATOR + PLATFORM + COLUMN)

- Characteristics of the indicator: see VC-50.
- Characteristics of the platform: see S-3545, M-4252, L-6080.

Model	SVC-50	MVC-50	LVC-50
Indicator	VC-50	VC-50	VC-50
Platform (cm)	35 x 45	42 x 52	60 x 80
Capacity (kg)	30, 60, 150	60, 150, 300	300, 600

**SVC-50
MVC-50
LVC-50**



CRANE SCALES 100 - 600 kg

**CR-100 / CR-200
DR-300 / DR-600**



- Capacity / Accuracy:
CR models: 100 kg – 50 g or 200 kg – 100 g.
DR models: 300 kg – 50 g or 600 kg – 100 g.
- Robust ABS housing.
- 16,5 mm LCD (CR) or double LCD backlight display (frontal/back), 5 digits 25 mm high (DR).
- Programs: zero, tare, unit conversion (kg/lb), hold, auto-off.
- Power: 3 AA batteries (CR models) or mains and rechargeable battery (DR models) (battery range: up to 35 hours, depending on use conditions).
- DR models are supplied with wireless remote control.

CRANE SCALES 2.000 - 5.000 kg

BH-2 / BH-5

- Capacity/accuracy:
2.000 kg - 1 kg or 5.000 kg - 2 kg.
- Display: LED - 1,2".
- Functions: zero, weight conversion (kg / lb), auto-off, hold display reading, divisions change.
- Rechargeable battery powered.
- Includes wireless remote controller.



WEIGHING PALLET TRUCK

TW



- Capacity/accuracy: 2.000 kg - 1 kg.
- Display: backlight LCD, 6 digit of 24 mm.
- 4 load cells.
- Functions: automatic zero tracking, weight conversion (kg / lb), pre-tare, gross/net weight and accumulation.
- Rechargeable battery powered.